

## PRODUCT DATA SHEET

Standing: 2021-12-21

LAUDA Puridest PD 8 G

Water still 400 V; 3/N/PE; 50/60 Hz

Part Number: L003019

### Features

- Glass Water Still for single distillation (fully automatic), suitable for both bench and wall mounting
- Distillate withdrawal through hose connection at the right-hand side.
- Evaporators, condensers and overflows are made of DURAN® / Borosilicate glass 3.3.
- Condensers with dribble guard.
- Sterillisation of the condensers by steam.
- Solenoid valve to control the water supply
- Economical energy consumption by distillation of the heated cooling water.
- Water saving through automatic water cut-off. Unnecessary water consumption will be avoided.
- Visible distillation process due to the easily removable, unbreakable front screen which does not steam up.
- CO<sub>2</sub> degassing through outlet in the condenser.
- Electronic level control during the whole distilling process.
- Water level control in the boiler automatically switches off the power in case of water shortage.
- Electronic impurity detector effects rinsing and cleaning of the evaporator by automatic water change.
- Quartz sheathed heating elements.
- Housing made of galvanised sheet steel, powder coated



Reserve technical changes

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen  
Postfach 1251 • 97912 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0 • F + 49 (0) 9343 503-222  
info@lauda.de • www.lauda.de  
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser

## PRODUCT DATA SHEET

Standing: 2021-12-21

LAUDA Puridest PD 8 G

Water still 400 V; 3/N/PE; 50/60 Hz

Part Number: L003019

### Technical Features

Conductivity stage 1 /25 °C	2.2 µS/cm
Production output	8 L/h
Heater power max.	6 kW
Power consumption max.	6 kW
Cooling water flow rate	2.4 L/min
Maximal pressure cooling water	7 bar
Wasserkühlung Zulauf für Schlauch	1/2 "
Wasserkühlung Ablauf für Schlauch	1/2 "
Overall dimensions (WxDxH)	650 x 365 x 390 mm
Weight	25 kg
Ambient temperature range	10 ... 40 °C
Power supply	400 V; 3/N/PE; 50/60 Hz
Power plug	Power cord with plug (IEC 60309, 5-pol, CEE, red, 16 A)

Reserve technical changes

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen  
Postfach 1251 • 97912 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0 • F + 49 (0) 9343 503-222  
info@lauda.de • www.lauda.de  
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser