## KERN HDB 10K10N

## Practical hanging scale for rapid, mobile weighing





Brand	KERN
Product categoriy	Industrial scale
Product group	Hanging scale
Product family	HDB
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	10 kg
Readability [d]	0,01 kg
Resolution	1.000
Linearity	± 0,03 kg
Reproducibility	0,01 kg
Default unit	kg
Units	kg Ib N
Adjustment options	Adjusting with external weight
Recommended adjusting weight	10 kg (M1)
Stabilization time	2 s
Warm-up time	10 min
Eccentric/Off-centre loading is not possible	$\checkmark$
Maximum creep (15 minutes)	20 g
Maximum creep (30 minutes)	40 g
Tolerance (% of [Max])	0,5%
Internal measuring frequency	5 Hz

1

Λ 1	$\mathbf{n}$	$\mathbf{n}$	r,	$\gamma$		2
A	Ы	Υ		5	v	а

CE mark

Display	
Display type	LCD
Display backlight	no
Display digit height	12 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	72×25×105 mm
Dimensions completely mounted (W×D×H)	72×25×188 mm
Material housing	plastic
Material load hook	steel
Functions	
Number of keys for operation	3
Tare function	manual (multi)
Hold function	✓
Function for averaging under unstable weighing conditions	1
Peak function	✓
Underfloor weighing	None
Power Supply	
Supplied power supply	Battery
Supplied power supply Battery	Battery 2×1.5 V AAA
Battery Battery / accumulator type	2×1.5 V AAA Alkali(-Manganese)
Battery Battery / accumulator type Battery capacity	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh
Battery Battery / accumulator type Battery capacity Battery voltage	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V
Battery Battery / accumulator type Battery capacity	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh
Battery Battery / accumulator type Battery capacity Battery voltage	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max]	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min]	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max]	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Min]	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max]	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max] Storage temperature [Max] Packing & Shipping	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C 60 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N)	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C 60 °C
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C 60 °C 1 d 225×150×70 mm 0,192 kg Parcel service
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method Net weight approx.	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C 60 °C 1 d 225×150×70 mm 0,192 kg Parcel service 0,20 kg
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method Net weight approx. Gross weight approx.	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C 35 °C -20 °C 60 °C 60 °C 1 d 225×150×70 mm 0,192 kg Parcel service 0,20 kg 0,45 kg
Battery Battery / accumulator type Battery capacity Battery voltage Battery operating time Environmental conditions Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method Net weight approx.	2×1.5 V AAA Alkali(-Manganese) 1.200 mAh 1,5 V 180 h 90 % 5 °C 35 °C -20 °C 60 °C 1 d 225×150×70 mm 0,192 kg Parcel service 0,20 kg

## KERN HDB 10K10N

Practical hanging scale for rapid, mobile weighing



Services (optional)	
Article number for adjustment at the location of installation	961-248
Article number for DAkkS calibration	963-128H

Article number for certificate of 969-517 conformity (verification)

## Pictograms

STANDARD



OPTION

